EPSA safety first

ADJUSTABLE TRACHEOSTOMY CANNULA WITH SUBGLOTTIC ASPIRATION



ADJUSTABLE TRACHEOSTOMY CANNULA WITH SUBGLOTTIC ASPIRATION

CODE: 9258

1 PVC cannula, right angle curved, flexible, transparent, longitudinal line opaque to X-rays polished distal orifice, atraumatic. Standard connector at proximal end. Fixation flange with lock ring, repositionable and adjustable. Low-pressure cuff, pilot balloon and retention valve. Suction channel, with orifice next to the upper edge of the cuff.

1 suction catheter.

1 velcro neck band.



Available Sizes

6,0 / 7,0 / 8,0 / 9,0 / 10,0 mm.

STERILE, SINGLE PACK, SINGLE USE.



Recommendation for use

Recommendation of a professional on the use of the technology. The Adjustable Tracheostomy Cannula with subglottic aspiration is indicated in patients who require mechanical ventilation due to functional, post-traumatic or surgical alterations that affect the patency of this sector of the airway.

Its purpose is:

- enable mechanical ventilation;
- allow endoscopic maneuvers (diagnostic and / or therapeutic in the airway);
- facilitate the humidification of secretions and endotracheal aspiration.

The cuff seals the tracheal lumen, allowing adequate control of gas movement during mechanical ventilation and preventing the passage of fluids and secretions from the upper airway into the bronchial tree.

It has a mobile fixation flange that can be adjusted in the chosen position in relation to the anatomical characteristics of the patient's neck.

It has an aspiration channel with a hole above the balloon that allows the tracheal secretions that accumulate in the subglottic space of the patient to be aspirated. Aspiration of subglottic secretions can be performed intermittently or continuously through a system that leads them to a reservoir.